

Replacement Instructions for PROBE

Tools required: Phillips Head Screwdriver, Slip Joint Pliers, 5/16" Nut Driver, Pliers, Knife, Safety Gloves, and Shop Towel.

OPTIONAL: Before beginning, pump any fluid from the machine out into buckets or empty fluid boxes. This will make changing the parts easier and provide a chance to clean out any sludge buildup that may be in the base.

****IMPORTANT NOTE:** For solid grey probe, **DO NOT** attempt to remove the white cap on the end of the probe.

1. **Unplug the SmartWasher.**
2. **See instructions for removing the sink before proceeding.**
3. On the outside of the machine, detach the control box lid by removing four screws with the Phillips head screwdriver.
4. On the inside of the machine, detach the heater box lid by removing four screws with the Phillips head screwdriver. **BE CAREFUL NOT TO DROP THE SCREWS INTO THE BASE.**
5. On the outside of the machine, use the pliers to disconnect the pump wires (left) from the control board. Feed pump wires through the bulkhead fitting into the heater box inside of the base. (Removing the pump wires will allow the probe connector to fit through the bulkhead fitting.) ***See diagram***
6. On the outside of the machine, disconnect the probe cable from the control board in the control box and feed the cable through the bulkhead fitting to the heater box inside of the base.
7. Using the slip joint pliers, unscrew the probe from the bottom of the heater box.
8. Remove probe and set aside.
9. Feed the cable to the new probe through the opening in the bottom of the heater box located inside of the base. Screw the probe into the fitting and use the slip joint pliers to secure connection.
10. Feed the probe cable through the bulkhead fitting into the control box on the outside of the base. Attach the connector to the control board. ***See diagram***
11. Feed the pump wires through the bulkhead fitting and reconnect to the control board (left) inside of the control box. From top to bottom, the wires should be: brown, blue, and yellow/green. ***See diagram***
12. Inside of the base, replace the heater box lid and tighten the screws using the Phillips head screwdriver. **BE CAREFUL NOT TO DROP THE SCREWS INTO THE BASE.**
13. Outside of the base, replace the control box lid and tighten the screws using the Phillips head screwdriver.
14. Replace the sink. (See attached Sink Installation Instructions)
15. Replace the fluid in the base of the SmartWasher. Plug unit into power source and test.

If you have any questions about these procedures or if your SmartWasher is configured differently than described in these instructions, PLEASE CALL CHEMFREE CUSTOMER SERVICE AT 1-800-521-7182 or visit us on the web at www.chemfree.com for more detailed instructions, including instructional videos.